

## 14.9 - 28 TD-19 TT

130 A6 (122 A8)




### Technical data

Tyre size	14.9 - 28	Tread pattern	TD-19
Ply rating	8 PR	Service description LI SS	130 A6 (122 A8)
Type (Tubeless/Tube Type)	TT	Tube	14.9-28
Permitted rims	W13 W12	Section width (mm)	378
Overall diameter (mm)	1365	Loaded static radius (mm)	627
Rolling circumference (mm)	4113	Water 75% (l)	
EAN code	8590341039187		

Tyre load capacity (kg) Tyre pressure (bar)				Speed (km/h)
1,00	1,20	1,50	1,80	
1905	2115	2395	2660	10
1630	1810	2050	2280	20
1360	1510	1710	1900	30
1090	1210	1370	1500	40

#### Notices:

30 km/h (up to 40 km/h) load values also apply for low-speed high-torque field work.

For intensive road transport at 40/30 km/h the pressure must be increased by 0.4 bar. Maximum inflation pressure should never be exceeded.

For harvesting machines and front-end loader tractor application the Inflation Pressure must be increased by 0.4 bar.

All load values are valid for ground slopes up to and including 20 % (11°). When operating on slopes greater than 20 %, contact the producer.

TL = Tubeless? may be used with a tube.

TT = Tube Type